## NSN 5320-00-063-7670

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-063-7670 **Head Style:** Hexagon **Head Height:** 0.113 inches Shank Diameter: Between 0.213 inches and 0.215 inches Shank Style: Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** 0.157 mils and 0.219 centimeters Width Across Flats: Between 0.332 inches and 0.346 inches Hardness Rating: 39.0 rockwell c bolt and 43.0 rockwell c bolt **Special Features:** Color green Material: Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and chromate sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl2 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve **Specification Data:** 80205-nas1755 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-std (military Standard):

A040a0

Mil-s-5626 spec.