## NSN 5320-00-063-7982

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-s-5626 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-063-7982 **Head Style:** Hexagon **Head Height:** 0.135 inches **Shank Diameter:** Between 0.274 inches and 0.276 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** 0.470 mils and 0.531 centimeters Width Across Flats: Between 0.367 inches and 0.375 inches Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut Material: Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response nut **Specification Data:** 80205-nas1751 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0