

View Online at <https://aerobasegroup.com/nsn/5320-00-063-9103>

**Head Style:**

Hexagon

**Head Height:**

0.113 inches

**Shank Diameter:**

Between 0.213 inches and 0.215 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film or wax

**Grip Length:**

0.595 mils and 0.656 centimeters

**Width Across Flats:**

Between 0.305 inches and 0.312 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Shear Strength:**

5240 double pounds per square inch

**Heat Treatment:**

Annealed

**Material:**

Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body

**Material Specification:**

Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

**Specification Data:**

80205-nas1751 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.