NSN 5320-00-063-9135

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-063-9135

| Fastener Length: |
|---|
| Between 0.526 inches and 0.556 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.103 inches and 0.113 inches |
| Shank Diameter: |
| Between 0.213 inches and 0.215 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Expansion Device: |
| Serrated stem-type w |
| Lubrication: |
| Dry film or wax |
| Grip Length: |
| Between 0.406 inches and 0.469 inches |
| Width Across Flats: |
| Between 0.305 inches and 0.312 inches |
| Hardness Rating: |
| 39.0 rockwell c nut and 43.0 rockwell c nut |
| Heat Treatment: |
| Annealed |
| Material: |
| Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve |
| Material Specification: |
| Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5614 assn |
| standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve |
| Surface Treatment: |
| Cadmium sleeve and passivate sleeve |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response nut |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-s-5626 spec. |