NSN 5320-00-063-9885

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-063-9885

Fastener Length:
Between 0.579 inches and 0.609 inches
Head Style:
Hexagon
Head Height:
0.160 inches
Shank Diameter:
Between 0.309 inches and 0.311 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Expansion Device:
Threaded stem
Grip Length:
Between 0.407 inches and 0.469 inches
Width Across Flats:
Between 0.429 inches and 0.437 inches
Hardness Rating:
39.0 rockwell c nut and 43.0 rockwell c nut
Material:
Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve
Material Specification:
Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn
standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve
Surface Treatment:
Cadmium sleeve and passivate sleeve
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response nut
Specification Data:
30205-nas1669 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A040a0
Mil-std (military Standard):
Mil-s-5626 spec.