## NSN 5320-00-063-9965

Blind Rivet - Page 1 of 1

Mil-s-6758 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-063-9965

Fastener Length:
Between 0.590 inches and 0.620 inches
Head Style:
Hexagon
Head Height:
Between 0.086 inches and 0.096 inches
Shank Diameter:
Between 0.163 inches and 0.165 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film or wax
Grip Length:
Between 0.469 inches and 0.531 inches
Width Across Flats:
Between 0.277 inches and 0.283 inches
Shear Strength:
1920 double pounds per square inch
Special Features:
Heat process mil-h-6088
Heat Treatment:
Annealed
Material:
Steel comp 4130 stem or steel comp 8740 stem or steel comp 4140 stem
Material Specification:
Qq-a-282 federal specification single material response body
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):