

View Online at <https://aerobasegroup.com/nsn/5320-00-069-4391>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.565 inches and 1.585 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-rivet, straight, threaded

Lubrication:

Cetyl alcohol

Grip Length:

Between 1.245 inches and 1.255 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

5280 double pounds per square inch

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 4140

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-5626 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Baqq-p-416, type 1, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.