## NSN 5320-00-074-4514



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-074-4514 Fastener Length: Between 0.616 inches and 0.656 inches **Head Style:** Hexagon **Head Height:** 0.135 inches **Shank Diameter:** Between 0.258 inches and 0.260 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 0.470 inches and 0.531 inches Width Across Flats: Between 0.367 inches and 0.375 inches Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response nut **Specification Data:** 80205-nas1669 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.