

View Online at <https://aerobasegroup.com/nsn/5320-00-078-9612>

**Fastener Length:**

Between 0.215 inches and 0.245 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.163 inches and 0.164 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.325 inches and 0.332 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film or paraffin wax

**Grip Length:**

Between 0.094 inches and 0.156 inches

**Hardness Rating:**

30.0 rockwell c nut and 45.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Self-locking

**Material:**

Iron alloy 660 sleeve

**Material Specification:**

Ams 5737 assn standard single material response sleeve or ams 5732 assn standard single material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Specification Data:**

80205-nas1762 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0