

View Online at <https://aerobasegroup.com/nsn/5320-00-084-0703>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.975 inches and 0.995 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.254 inches and 0.255 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.390 inches and 0.395 inches

Grip Length:

0.510 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Solid film and cetyl alcohol lubrication

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response or ti-dize type 2, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0