NSN 5320-00-084-0710

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-084-0710 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.588 inches and 0.608 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.194 inches and 0.195 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches **Grip Length:** 0.198 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Solid film and cetyl alcohol lubrication Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-00-084-0710

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0