NSN 5320-00-084-2083

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-084-2083



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.623 inches and 0.643 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.080 inches and 0.081 inches

Shank Diameter:

Between 0.225 inches and 0.226 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

0.198 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Solid film and cetyl alcohol lubrication

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-00-084-2083

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

