

View Online at <https://aerobasegroup.com/nsn/5320-00-090-0781>

**Fastener Length:**

Between 0.741 inches and 0.771 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.125 inches and 0.135 inches

**Shank Diameter:**

Between 0.264 inches and 0.265 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Grease film

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Width Across Flats:**

Between 0.367 inches and 0.375 inches

**Hardness Rating:**

39.0 rockwell c bolt and 43.0 rockwell c bolt

**Shear Strength:**

9300 double pounds per square inch

**Heat Treatment:**

Annealed

**Material:**

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and chromate sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.