NSN 5320-00-091-5881

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-091-5881 **Fastener Length:** 1.610 inches **Head Style:** Undercut pan no. 2 **Head Height:** Between 0.195 inches and 0.205 inches **Shank Diameter:** Between 0.372 inches and 0.374 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.580 inches and 0.627 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 1.281 inches and 1.345 inches **Hardness Rating:** 48.0 rockwell c stem and 53.0 rockwell c stem Material: Steel comp 8740 stem **Material Specification:** 66 federal standard 1st material response mechanical lock or 66 federal standard 2nd material response mechanical lock or 66 federal standard 3rd material response mechanical lock or 66 federal standard 4th material response mechanical lock or 66 federal standard 5th material response mechanical lock or ams 5737 assn standard 6th material response mechanical lock **Surface Treatment:** Cadmium mechanical lock or passivate mechanical lock **Surface Treatment Specification:** Qq-p-416, type 2 federal specification 1st treatment response mechanical lock or qq-p-35 federal specification 2nd treatment response mechanical lock Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.