NSN 5320-00-093-7442Solid Rivet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5320-00-093-7442 |
|--|
| Fastener Length: |
| Between 1.115 inches and 1.135 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.155 inches and 0.160 inches |
| Shank Style: |
| Straight |
| Head Major Diameter: |
| Between 0.240 inches and 0.247 inches |
| Shear Strength: |
| 49000 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Nickel alloy 400 |
| Material Specification: |
| Qq-n-281 federal specification single material response |
| Surface Treatment: |
| Cadmium |
| |
| Surface Treatment Specification: |
| Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response |
| - |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a |
| Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: |