

View Online at <https://aerobasegroup.com/nsn/5320-00-097-5438>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.114 inches and 1.134 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.064 inches and 0.065 inches

Shank Diameter:

Between 0.163 inches and 0.164 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.287 inches and 0.292 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.817 inches

Thready Qty Per Inch (tpi):

36

Thread Size:

0.164 inches

Shear Strength:

1760 double pounds per square inch

Countersink Angle:

100.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.