
NSN 5320-00-098-0334

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.187 inches and 1.207 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.190 inches and 0.193 inches

Shank Diameter:

Between 0.436 inches and 0.437 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.668 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.567 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 431

Material Specification:

Ams5628 assn standard 1st material response or mil-s-18732 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-00-098-0334

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

