

View Online at <https://aerobasegroup.com/nsn/5320-00-103-0725>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.573 inches and 0.593 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.077 inches and 0.090 inches

**Width Between Flats:**

Between 0.095 inches and 0.097 inches

**Shank Diameter:**

Between 0.249 inches and 0.250 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**End Application:**

Wsd: helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, sof/hh-53h pave low; helicopter, advance attack, ah-1w; aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130); helicopter, uscg search and rescue, hh-60j; joint stars target radar system; helicopter, search and rescue, hh-60h; aircraft, c-2a (reprocured)

**Grip Length:**

0.193 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Material:**

Steel comp 4340 or steel comp 8735

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0