

View Online at <https://aerobasegroup.com/nsn/5320-00-103-0725>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.573 inches and 0.593 inches

Head Style:

Straight pan

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

End Application:

Wsd: helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, sof/hh-53h pave low; helicopter, advance attack, ah-1w; aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130); helicopter, uscg search and rescue, hh-60j; joint stars target radar system; helicopter, search and rescue, hh-60h; aircraft, c-2a (reprocured)

Grip Length:

0.193 inches

Thread Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Material:

Steel comp 4340 or steel comp 8735

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0