NSN 5320-00-107-2990

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-107-2990 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.345 inches and 1.365 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches Shank Style: **Head Major Diameter:** Between 0.297 inches and 0.302 inches **Grip Length:** 1.005 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 4340 or steel comp e4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-00-107-2990

Pin-rivet - Page 2 of 2



Fiig:

A528u0