## NSN 5320-00-109-0295

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-109-0295

| Factoner Langth   |
|---|
| Fastener Length:  |
| 1.756 inches  |
| Head Style:   |
| Undercut pan no. 2  |
| Head Height:  |
| Between 0.131 inches and 0.141 inches   |
| Shank Diameter:   |
| Between 0.310 inches and 0.312 inches   |
| Shank Style:  |
| Self-plugging mechanically locked stem  |
| Head Major Diameter:  |
| Between 0.480 inches and 0.522 inches   |
| Expansion Device:   |
| Serrated stem-type w  |
| Grip Length:  |
| Between 1.469 inches and 1.532 inches   |
| Hardness Rating:  |
| 48.0 rockwell c and 53.0 rockwell c stem  |
| Shear Strength:   |
| 8500 single pounds per square inch  |
| Material:   |
| Steel comp 4037 or steel comp 4027 or steel comp 4130 sleeve  |
| Material Specification:   |
| Astm a547 assn standard 1st material response or 66 federal standard 2nd material response or mil-s-6758 military specification 3rd |
| material response or 66 federal standard 3rd material response sleeve   |
| Surface Treatment:  |
| Cadmium and chromate sleeve   |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 3 federal specification single treatment response sleeve   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
| Mil-std (military Standard):  |
| Mil-s-6758 spec.  |
|   |