

View Online at <https://aerobasegroup.com/nsn/5320-00-109-0295>

Fastener Length:

1.756 inches

Head Style:

Undercut pan no. 2

Head Height:

Between 0.131 inches and 0.141 inches

Shank Diameter:

Between 0.310 inches and 0.312 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.480 inches and 0.522 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.469 inches and 1.532 inches

Hardness Rating:

48.0 rockwell c and 53.0 rockwell c stem

Shear Strength:

8500 single pounds per square inch

Material:

Steel comp 4037 or steel comp 4027 or steel comp 4130 sleeve

Material Specification:

Astm a547 assn standard 1st material response or 66 federal standard 2nd material response or mil-s-6758 military specification 3rd material response or 66 federal standard 3rd material response sleeve

Surface Treatment:

Cadmium and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.