## NSN 5320-00-109-0359

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-109-0359



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.332 inches and 1.357 inches

## Head Style:

Err-090

#### Head Height:

Between 0.044 inches and 0.056 inches

## Shank Diameter:

0.2322 inches

## Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

Between 0.340 inches and 0.352 inches

#### **Tip Diameter:**

0.2120 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

Between 1.052 inches and 1.067 inches

### Min. Tensile Strength (psi):

180000 pounds per square inch

#### Thread Size:

0.190 inches

#### Shear Strength:

108000 single pounds per square inch

#### Material:

Steel comp 8740 or steel comp 4340

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-00-109-0359

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

