

View Online at <https://aerobasegroup.com/nsn/5320-00-117-6939>

**Fastener Length:**

Between 0.302 inches and 0.322 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.093 inches and 0.097 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.175 inches and 0.183 inches

**End Application:**

W/s: teammate, an/trq-32; radar set, an/tpn-18; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); communications terminal, satellite an/gsc-3 (v)1; traffic jam, an/tlq-17a; aircraft, thunderbolt ii, a-10; support equipment, b-52 aircraft; support equipment, b-1 aircraft; missile, advanced medium range air-to-air (amraam) /aim120a

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Heat Treatment:**

T-4 solution heat treated

**Material:**

Aluminum alloy 2117

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.