

View Online at <https://aerobasegroup.com/nsn/5320-00-117-6948>

Fastener Length:

Between 0.178 inches and 0.198 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

Between 0.221 inches and 0.229 inches

End Application:

W/s: helicopter, mh-53e; missile, all-weather anti-ship, harpoon (agm-84); switching unit, telephone, auto; helicopter, advance attack, ah-1w; helicopter, search and rescue, hh-60h; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, c-2a (reprocured); missile, air-to-air, phoenix (aim-54); helicopter, carrier based asw, sh-60f

Shear Strength:

26000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Material:

Aluminum alloy 2117

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.