

View Online at <https://aerobasegroup.com/nsn/5320-00-117-6948>

**Fastener Length:**

Between 0.178 inches and 0.198 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**End Application:**

W/s: helicopter, mh-53e; missile, all-weather anti-ship, harpoon (agm-84); switching unit, telephone, auto; helicopter, advance attack, ah-1w; helicopter, search and rescue, hh-60h; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, c-2a (reprocured); missile, air-to-air, phoenix (aim-54); helicopter, carrier based asw, sh-60f

**Shear Strength:**

26000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 2117

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.