

View Online at <https://aerobasegroup.com/nsn/5320-00-117-6950>

**Fastener Length:**

Between 0.302 inches and 0.322 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**End Application:**

W/s: deff comm meteorol (an/tmq-028, an/tcc-76, an/tps-068, an/tcc-77); aircraft, ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; airborne mobile dir air spt ctl (2id), (02mjul83)(an/uyq-3a); support equipment, b-52 aircraft; missile, advanced medium range air-to-air (amraam)/aim120a; communications terminal, satellite an/gsc-3 (v)1; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p) ; central message switch, an/tyc-39a

**Grip Length:**

0.124 inches

**Shear Strength:**

26000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 2117

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.