NSN 5320-00-117-6953

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-117-6953

view Online at https://aerobasegroup.com/nsn/5320-00-117-6953
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.124 inches and 0.128 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.221 inches and 0.229 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Shear Strength:
26000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Criticality Code Justification:
Feat
Special Features:
The item is a flight safety critical aircraft part (fscap).
Material:
Aluminum alloy 2117
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Oxide film or anodize
Surface Treatment Specification:
Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-c-5541 spec.