

View Online at <https://aerobasegroup.com/nsn/5320-00-117-6959>

**Fastener Length:**

Between 1.115 inches and 1.135 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**End Application:**

W/s: f/a-18e/f hornet aircraft; fms-aircraft, hawkeye e-2c; los angeles class ssn (688); aircraft, c-2a (reprocured); missile, advanced medium range air-t0-air (amraam)/aim120a; aircraft, airlifter c-17a; missile, minuteman lgm-30; joint stars target radar system; missile, all-weather ant-ship, harpoon (agm-84); engine, aircraft, t56-a-7/15 (c-130b/e/h/n/p)

**Grip Length:**

Between 0.927 inches and 0.947 inches

**Shear Strength:**

26000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 2117

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.