# NSN 5320-00-117-7206

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-117-7206

# Fastener Length:

Between 0.240 inches and 0.260 inches

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.124 inches and 0.128 inches

## Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

Between 0.221 inches and 0.229 inches

#### Grip Length:

0.052 mils and 0.072 centimeters

#### Shear Strength:

41000 single pounds per square inch

#### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

#### Heat Treatment:

T-73 solution heat treated

# Material:

Aluminum alloy 7050

#### Material Specification:

Qq-a-430 federal specification single material response

## Surface Treatment:

Anodize or chromate

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

# Unit Of Measure:

```
---
```

#### Demilitarization:

No

Fiig:

#### A040a0

Mil-std (military Standard):

Mil-a-8625 spec.