## NSN 5320-00-117-7238

Solid Rivet - Page 1 of 1



View Online at https://aeroba n/nsn/5320-00-117-7238

View Online at https://aerobasegroup.com/nsn/5320-00-117-7238
Fastener Length:
Between 0.615 inches and 0.635 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.249 inches and 0.253 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.472 inches and 0.480 inches
Grip Length:
0.240 mils and 0.260 centimeters
Shear Strength:
41000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize or chromate
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.