NSN 5320-00-117-7512

Solid Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-117-7512

view Online at https://aerobasegroup.com/nsn/5320-00-117-7512	
Fastener Length:	
Between 1.115 inches and 1.135 inches	
Head Style:	
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)	
Shank Diameter:	
Between 0.186 inches and 0.190 inches	
Shank Style:	
Straight w/radius chamfered tip	
Head Major Diameter:	
Between 0.349 inches and 0.357 inches	
Grip Length:	
0.834 mils and 0.854 centimeters	
Shear Strength:	
26000 single pounds per square inch	
Countersink Angle:	
Between 99.5 degrees and 100.5 degrees	
Material:	
Aluminum alloy 2117	
Material Specification:	
Qq-a-430 federal specification single material response	
Surface Treatment:	
Anodize or oxide film	
Surface Treatment Specification:	
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response	зe
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A040a0	