## NSN 5320-00-119-6821

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-119-6821

| Fastener Length:   |
|--|
| Between 0.990 inches and 1.010 inches  |
| Head Style:  |
| Universal  |
| Head Height:   |
| Between 0.040 inches and 0.050 inches  |
| Shank Diameter:  |
| Between 0.093 inches and 0.097 inches  |
| Shank Style:   |
| Straight   |
| Head Major Diameter:   |
| Between 0.178 inches and 0.196 inches  |
| Grip Length:   |
| Between 0.849 inches and 0.869 inches  |
| Shear Strength:  |
| 24000 single pounds per square inch  |
| Material:  |
| Aluminum alloy 5056  |
| Material Specification:  |
| Qq-a-430 federal specification single material response  |
| Surface Treatment:   |
| Anodize or oxide film  |
| Surface Treatment Specification:   |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-a-8625 spec.   |
|  |