NSN 5320-00-119-8351

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-119-8351 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.645 inches and 0.670 inches **Head Style:** Err-090 **Head Height:** Between 0.044 inches and 0.056 inches **Shank Diameter:** 0.2114 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.312 inches and 0.323 inches **Tip Diameter:** 0.2055 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.365 inches and 0.380 inches Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf ıre:

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5320-00-119-8351

Pin-rivet - Page 2 of 2



Fiig:

A528u0