

View Online at <https://aerobasegroup.com/nsn/5320-00-129-9706>

Fastener Length:

Between 0.222 inches and 0.252 inches

Head Style:

Universal

Head Height:

Between 0.030 inches and 0.040 inches

Shank Diameter:

0.125 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.238 inches and 0.262 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.063 inches and 0.125 inches

Shear Strength:

485 single pounds per square inch

Material:

Steel comp 1012 mandrel or steel comp 1013 mandrel or steel comp 1015 mandrel or steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel or steel comp 1023 mandrel or steel comp 1524 mandrel or steel comp 1025 mandrel or steel comp 1045 mandrel or steel comp 1046 mandrel or steel comp 1548 mandrel or steel comp 1049 mandrel or steel comp 1551 mandrel or steel comp 1552 mandrel or steel comp 1053 mandrel or steel comp 1055 mandrel or steel comp 1059 mandrel or steel comp 1060 mandrel or steel comp 1561 mandrel or steel comp 1064 mandrel or steel comp 1065 mandrel or steel comp 1566 mandrel or steel comp 1069 mandrel or steel comp 1070 mandrel or steel comp 1572 mandrel or steel comp 1074 mandrel or steel comp 1075 mandrel

Material Specification:

Qq-s-763 federal specification single material response mandrel

Surface Treatment:

Passivate mandrel

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-r-24243 spec.