

View Online at <https://aerobasegroup.com/nsn/5320-00-134-4017>

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.1635 inches and 0.1645 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Carbo wax or cetyl alcohol or dry film

Grip Length:

Between 0.407 inches and 0.469 inches

Width Across Flats:

Between 0.244 inches and 0.250 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Heat Treatment:

Annealed

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.