

View Online at <https://aerobasegroup.com/nsn/5320-00-136-2957>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.595 inches and 0.615 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.055 inches and 0.075 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Grip Length:**

Between 0.156 inches and 0.250 inches

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

1.065 in. Long serrated break stem on shank end

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.