

View Online at <https://aerobasegroup.com/nsn/5320-00-136-2957>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.595 inches and 0.615 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.075 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

Between 0.156 inches and 0.250 inches

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

1.065 in. Long serrated break stem on shank end

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.