

View Online at <https://aerobasegroup.com/nsn/5320-00-143-6058>

**Fastener Length:**

Between 0.652 inches and 0.682 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.373 inches and 0.375 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.696 inches and 0.762 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.407 inches and 0.469 inches

**Hardness Rating:**

30.0 rockwell c nut and 45.0 rockwell c nut

**Shear Strength:**

15750 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Iron alloy 660 sleeve

**Material Specification:**

Ams 5737 assn standard single material response sleeve or ams 5732 assn standard single material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Specification Data:**

80205-nas1672 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0