NSN 5320-00-143-6066

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-143-6066

View Online at https://aerobasegroup.com/nsn/5320-00-143-
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.174 inches and 0.196 inches
Head Minor Diameter:
0.134 mils and 0.144 centimeters
Countersink Height:
0.029 inches
Shear Strength:
37000 single pounds per square inch
Countersink Angle:
Between 70.0 degrees and 130.0 degrees
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
ΔΩΛΩ

Mil-c-5541 spec.

Mil-std (military Standard):