

View Online at <https://aerobasegroup.com/nsn/5320-00-143-6234>

**Fastener Length:**

0.545 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Self-plugging

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Tw/s: tarawa class lha; wasp class lhd; aircraft, hercules c-130; aircraft, phantom f-4; nimitz class cvn; lpd-17 class amphibious transport dock; forrestal class cv; fms-a7 aircraft; aircraft, stratofortress b-52; kidd class ddg

**Grip Length:**

Between 0.376 inches and 0.437 inches

**Shear Strength:**

370 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Aluminum alloy 2017 stem

**Material Specification:**

Qq-a-430 federal specification single material response stem

**Surface Treatment:**

Anodize stem or anodize stem or chromate stem

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.