

View Online at <https://aerobasegroup.com/nsn/5320-00-143-6234>

Fastener Length:

0.545 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Expansion Device:

Serrated stem-type w

End Application:

Tw/s: tarawa class lha; wasp class lhd; aircraft, hercules c-130; aircraft, phantom f-4; nimitz class cvn; lpd-17 class amphibious transport dock; forrestal class cv; fms-a7 aircraft; aircraft, stratofortress b-52; kidd class ddg

Grip Length:

Between 0.376 inches and 0.437 inches

Shear Strength:

370 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Aluminum alloy 2017 stem

Material Specification:

Qq-a-430 federal specification single material response stem

Surface Treatment:

Anodize stem or anodize stem or chromate stem

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.