

View Online at <https://aerobasegroup.com/nsn/5320-00-143-6461>

Fastener Length:

Between 0.804 inches and 0.834 inches

Head Style:

Hexagon

Head Height:

Between 0.122 inches and 0.138 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded mandrel

Lubrication:

Grease film

Grip Length:

Between 0.657 inches and 0.719 inches

Width Across Flats:

Between 0.365 inches and 0.377 inches

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Shear Strength:

95000 single pounds per square inch

Material:

Steel comp 8740 nut or steel comp 8740 nut or steel comp 4130 nut or steel comp 4340 nut or steel comp e4340 nut or steel nut

Material Specification:

Mil-s-6049 military specification 1st material response nut or ams 6322 assn standard 2nd material response nut or mil-s-6758 military specification 3rd material response nut or mil-s-5000 military specification 4th material response nut or ams 6407 assn standard 5th material response nut

Test Data Document:

77272-bacb30ay +80.70.6.2.2 and +80.70.6.2.3 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.