NSN 5320-00-145-1799

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-145-1799

view Offiline at https://acrobasegroup.com/hish/05/20-00-140-1705
Fastener Length:
Between 0.535 inches and 0.555 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.217 inches and 0.218 inches
Shank Style:
Self-plugging shank w/grooved end for locking
Head Major Diameter:
0.305 inches
Expansion Device:
Drive stem-type h
Lubrication:
Grease film
Grip Length:
Between 0.478 inches and 0.540 inches
Shear Strength:
75000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 431 sleeve
Material Specification:
Mil-s-18732 military specification single material response sleeve
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416 type 1 cl 3 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-s-18732 spec.