## NSN 5320-00-147-1647

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-147-1647

Fastener I	Length:
------------	---------

Between 0.212 inches and 0.232 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.125 inches and 0.129 inches

**Shank Style:** 

Self-plugging shank w/grooved end for locking

**Head Major Diameter:** 

Between 0.207 inches and 0.225 inches

**Expansion Device:** 

Serrated stem-type w

**Grip Length:** 

Between 0.104 inches and 0.128 inches

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

Material:

Aluminum alloy 5056 sleeve

**Material Specification:** 

Qq-a-430 federal specification single material response stem

**Surface Treatment:** 

Anodize stem or chromate stem

**Surface Treatment Specification:** 

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.