

View Online at <https://aerobasegroup.com/nsn/5320-00-150-4120>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.638 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

0.188 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

0.313 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

108000 single pounds per square inch

Heat Treatment:

As fabricated

Material:

Steel comp 8740 or steel comp 4140

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

Surface Treatment:

Cadmium and phosphate

Surface Treatment Specification:

Qq-p-416 type 3 cl 1 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.