NSN 5320-00-150-4221

Pin-rivet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5320-00-150-4221 |
|--|
| Fastener Length: |
| Between 0.443 inches and 0.453 inches |
| Head Style: |
| Straight pan |
| Head Height: |
| Between 0.028 inches and 0.040 inches |
| Shank Diameter: |
| Between 0.124 inches and 0.125 inches |
| Shank Style: |
| Stump |
| Head Major Diameter: |
| Between 0.181 inches and 0.195 inches |
| Grip Length: |
| Between 0.189 inches and 0.250 inches |
| Features Provided: |
| Casehardened |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 76.1 rockwell superficial 15-n and 80.9 rockwell superficial 15-n |
| Shear Strength: |
| 1150 single pounds per square inch |
| Special Features: |
| Rockwell cscale 37 min 41 maximum core hardness |
| Material: |
| Steel comp 4037 or steel comp 4140 or steel comp 8740 |
| Material Specification: |
| Qq-w-405 federal specification all material responses |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Specification Data: |
| 80205-nas1424 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |

Fiig:

. -

A528u0