
# NSN 5320-00-151-5450

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.347 inches and 2.367 inches

## Head Style:

Err-090

## Head Height:

Between 0.078 inches and 0.088 inches

## Width Between Flats:

Between 0.158 inches and 0.162 inches

## Shank Diameter:

Between 0.374 inches and 0.375 inches

Shank Style:

## Head Major Diameter:

Between 0.565 inches and 0.600 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

1.817 inches

# Thread Size:

0.375 inches

## Shear Strength:

125000 single pounds per square inch

Material:

Steel comp 431

## **Material Specification:**

Mil-s-18732 military specification single material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-00-151-5450

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

