

View Online at <https://aerobasegroup.com/nsn/5320-00-151-5460>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.815 inches and 0.835 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.297 inches and 0.302 inches

**End Application:**

W/s: aircraft, prowler ea-6b; global hawk high altitude-long endurance unmanned aerial vehicle; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, tomcat f-14; aircraft, galaxy c-5; aircraft, thunderbolt ii, a-10; aircraft, f-111; aircraft, stratalifter c-135; aircraft, hornet f/a-18; aircraft, eagle f-15

**Grip Length:**

0.505 inches

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0