

View Online at <https://aerobasegroup.com/nsn/5320-00-151-5460>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.815 inches and 0.835 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.297 inches and 0.302 inches

End Application:

W/s: aircraft, prowler ea-6b; global hawk high altitude-long endurance unmanned aerial vehicle; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, tomcat f-14; aircraft, galaxy c-5; aircraft, thunderbolt ii, a-10; aircraft, f-111; aircraft, stratalifter c-135; aircraft, hornet f/a-18; aircraft, eagle f-15

Grip Length:

0.505 inches

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0